

Lehto



BOB is a LED spot with double joint that allows an inclination of 90° on the horizontal plane and a rotation of 360° around the vertical axis. Aluminum structure and heat sink. Easy replacement of secondary lens.

BOB è uno spot LED con doppio snodo che permette un'inclinazione di 90° sul piano orizzontale e una rotazione di 360° attorno all'asse verticale. Struttura e dissipatore in alluminio. Facile sostituzione dell'ottica secondaria.

NODO BOB



LED adjustable light source
Sorgente LED orientabile

1 LED x 20W - 230V

2700K CRI 97 - 1800 lm

50380 White Bianco
50580 Black Nero

3000K CRI 97 - 1900 lm


50381 White Bianco
50581 Black Nero

To be completed with lenses
Da completare con ottiche

51102 30°
51104 40°
51106 60°
51108 Oval
51110 Rectangular
51112 Wallwasher

Power-supply included
Dimmable cut-phase

Alimentatore incluso
Dimmerabile taglio di fase



IP20
Kg 0.80




GU10 adjustable light source
Sorgente orientabile GU10

GU10 - 230V
MAX 10W LED

50390 White Bianco
50590 Black Nero

The dimensions of the lamp body have been designed to contain the 50 mm diameter GU10 socket bulbs with SMART technology [Philips HUE, Amazon Alexa, Google Home, Apple Home].

I dimensionamenti del corpo lampada sono stati studiati per contenere le lampadine attacco GU10 diametro 50 mm con tecnologia SMART [Philips HUE, Amazon Alexa, Google Home, Apple Home].



IP20
Kg 0.84



BOB is a LED spot with double joint that allows an inclination of 90° on the horizontal plane and a rotation of 360° around the vertical axis. Aluminum structure and heat sink. Easy replacement of secondary lens. Optics: 30°, 40°, 60°, oval, rectangular, Wallwasher. Different shade LEDs [2700K, 3000K and others on request] CRI 90 version. Integrated dimmable cut-phase power supply. Photometric measure LETROH.com

BOB è uno spot LED con doppio snodo che permette un'inclinazione di 90° sul piano orizzontale e una rotazione di 360° attorno all'asse verticale. Struttura e dissipatore in alluminio. Facile sostituzione dell'ottica secondaria. Ottiche: 30°, 40°, 60°, ovale, rettangolare, Wallwasher. LED di differenti tonalità [2700, 3000K e altre su richiesta] CRI 90. Alimentatore dimmerabile a taglio di fase integrato. Curve fotometriche LETROH.com



LETROH Srl

Via Cadorna 15
20073 Opera [Milano] Italia

contact@letroh.com
letroh.com



ELECTROSOPHY O5